



LCD type

FND type



Smart phone application (Bluetooth Option)



TF-100




TF-400

ZigBee Controller (Option)



IR controller (Standard)



FEATURE

- ◆ Water proof : IP-66
- ◆ Swivel hook
- ◆ Lightweight & easy to carry
- ◆ Big size display
- ◆ Built-in high capacity lithium polymer battery
- ◆ Bluetooth , ZigBee wireless communication (Optional)

MODEL	DIMMENSION			
	H	A	W	B
TCG - 500K	361	41	34	19
TCG - 1T	406	50	43	21
TCG - 2T	488	61	51	31
TCG - 3T	488	61	51	31

MODEL	TCG-500K	TCG-1T	TCG-2T	TCG-3T	TCG-500KL	TCG-1TL	TCG-2TL	TCG-3TL
Capacity	500kg	1,000kg	2,000kg	3,000kg	500kg	1,000kg	2,000kg	3,000kg
Division	0.1/0.2kg	0.5kg	1kg	1kg	0.1/0.2kg	0.5kg	1kg	1kg
Max. Tare Weight	500kg	1,000kg	2,000kg	3,000kg	500kg	1,000kg	2,000kg	3,000kg
Product weight	2.8kg	3.6kg	7kg	7kg	2.8kg	3.6kg	7kg	7kg
Display	5digit, 30.4mm FND				6 digit, 30mm FSTN LCD / LED Backlight			
Operating time	Approx.60hr				Approx.200hr (Backlight off)			
Battery	Lithium Polymer Battery 7.4V				Lithium Polymer Battery 3.7V			
Charging Adaptor	DC 12V, 1A SMPS				DC 5V, 1A SMPS			
Temperature range	-10 °C ~ 40 °C							
Water proof Level	IP-65							
Keypad	Power , Zero , Tare , Hold , *							
Display Lamp	Low Battery, Zero, Tare, Hold, Stable							
Parts	Charging Adaptor, Infrared remote controller							
Case Material	Engineering plastic							